# PROJECT DESCRIPTION

#### GENERAL

THIS PROJECT INVOLVES THE RECONSTRUCTION OF THE EXISTING TRAFFIC CONTROL SIGNAL AT THE INTERSECTION OF MD 589 (RACETRACK ROAD) AND CATHELL ROAD IN WORCESTER COUNTY, MD 589 IS ASSUMED TO RUN IN A NORTH-SOUTH DIRECTION.

#### INTERSECTION OPERATION

THE INTERSECTION WILL OPERATE IN A NEMA EIGHT-PHASE, FULL-TRAFFIC-ACTUATED MODE WITH THE MD 589 APPROACHES OPERATING CONCURRENTLY AND THE CATHEL ROAD APPROACHES OPERATING CONCURRENTLY.

EXCLUSIVE/PERMISSIVE LEFT-TURN PHASING IS PROVIDED FOR NORTHBOUND AND SOUTHBOUTH MD 589.

EXCLUSIVE/PERMISSIVE LEFT-TURN PHASING WILL BE PROVIDED FOR EASTBOUND AND WESTBOUND CATHELL ROAD APPROACHES.

A RIGHT-TURN OVER-LAP PHASE WILL BE PROVIDED FOR EASTBOUND CATHELL ROAD APPROACH.

#### CONTROLLER REQUIREMENTS

INSTALL A FULL-TRAFFIC-ACTUATED, EIGHT-PHASE CONTROLLER WITH ONE (1) FOUR-CHANNEL, TIME-DELAY-OUTPUT LOOP DETECTOR AMPLIFIERS, INTERSECTION MONITOR WITH BATTERY BACKUP FOR PHONE DROP AND ASSOCIATED HARNESSES HOUSED IN A NEMA SIZE "6" BASE MOUNTED CABINET.

### MAINTENANCE OF TRAFFIC

THE FOLLOWING TRAFFIC CONTROL STANDARDS SHALL BE REFERENCED FOR THE PROJECT.

STANDARD NO. MD-104.00 - 104.00-30

STANDARD NO. MD-104.37-01 (LEFT LANE CLOSURE)

STANDARD NO. MD-104.38-01 (RIGHT LANE CLOSURE) STANDARD NO. MD-104.41-01 (INTERSECTION FAR-RIGHT

LANE CLOSURE) STANDARD NO. MD-104.43-01 (SHOULDER WORK)

STANDARD NO. MD-104.44-01 (LEFT LANE CLOSURE)

# PROJECT CONTACTS

THE CONTACT PERSONS FOR SHA ARE AS FOLLOWS:

MR. GENE COFIELL ASSISTANT DISTRICT ENGINEER - TRAFFIC PHONE: (410) 677-4040

MR. JAMES R. WRIGHT ASSISTANT DISTRICT ENGINEER - MAINTENANCE PHONE: (410) 677-4010

MR. BRUCE W. POOLE DISTRICT UTILITY ENGINEER PHONE: (410) 677-4082

MR. RICHARD L. DAFF, SR. CHIEF, TRAFFIC OPERATIONS DIVISION PHONE: (410) 787-7630

L,M,P,R

STANDARD NO. MD-104.45-01 (RIGHT LANE CLOSURE)


STANDARD NO. MD-104.46-01 (CENTER LANE CLOSURE)

BAY LANE CLOSURE)

STANDARD NO. MD-104.48-01 (INTERSECTION TURN

STANDARD NO. MD-104.49-01 (SHOULDER WORK)

# WIRING DIAGRAM




> MICROLOOP PROBE LEAD-IN STRANDED BARE COPPER GROUND WIRE (NO. 6 A.W.G.)

5-CONDUCTOR ELECTRICAL CABLE (NO. 14 A.W.G.)

ML - MICROLOOP PROBE SET + - 3/4 IN. X 10 FT. GROUND ROD

W VIDEO DETECTION
N LEAD-IN CABLE



# EQUIPMENT LIST "A"

### A. EQUIPMENT TO BE SUPPLIED BY THE SHA


CAT. CODE	QUANTITY	DESCRIPTION
900000	1 EACH	FOUR-CHANNEL, TIME-DELAY-OUTPUT, LOOP DETECTOR AMPLIFIER
900000	1 EACH	VIDEO INTERFACE EQUIPMENT
900000	1 EACH	BASE MOUNTED CABINET/CONTROLLER
900000	1 EACH	STEEL MAST ARM POLE WITH TWIN 50/70 FT. MAST ARM
973023	176 S.F.	SHEET ALUMINUM SIGNS TO CONSIST OF :
		- 4 EACH R10-12 SIGN (36 IN. x 42 IN.) - MAST ARM MOUNT
		- 4 EACH D-3(1) SIGN (VARIABLE × 16 IN.) DUAL FACED - MAST ARM MOUNT
		- 1 EACH ASSOCIATED SHIELD ASSEMBLY "NORTH, MD 589, RIGHT ARROW (30 IN. x 51 IN.) - POLE MOUNT
		- 1 EACH ASSOCIATED SHIELD ASSEMBLY "NORTH, MD 589, LEFT ARROW" (48 IN. × 75 IN.) - POLE MOUNT
		- 1 EACH ASSOCIATED SHIELD ASSEMBLY "SOUTH, MD 589, RIGHT ARROW (30 IN. x 51 IN.) - POLE MOUNT
		- 1 EACH ASSOCIATED SHIELD ASSEMBLY "SOUTH, MD 589, LEFT ARROW" (48 IN. x 75 IN.) - POLE MOUNT
		- 1 EACH R3-5L (30 IN. X 36 IN.) - MAST ARM MOUNT
		- 1 EACH R3-5R (30 IN. X 36 IN.) - MAST ARM MOUNT

## EQUIPMENT LIST "C"

### C. EQUIPMENT TO BE REMOVED AND RETURNED TO SHA

ALL REMOVED SIGNAL MATERIALS SHALL BECOME PROPERTY OF THE CONTRACTOR

# PHASE CHART



PHASE I + 5	<b>←</b> R —	R G —	R	R G —	<b>R</b> G—	R	R	R	R G→	R	R	R		
I + 5 CHANGE	PHASE	1 + 5	MAY	CHANGE	TO P	'HASE	1 + 6,	PHASE	2 + 5	OR P	HASE	2 + 6		, Т
PHASE I + 6	<b>←</b> G —	<b>←</b> G —	G	R	R	R	R	R	R G→	R	R	R	4	۲
I + 6 CHANGE	<b>←</b> G —	<b>←</b> <sup>G</sup> —	G	R	R	R	R	R		R	R	R		_►
PHASE 2 + 5	R	R	R	<b>G</b> G —	<b>←</b> G —	G	R	R	R	R	R	R		
2 + 5 CHANGE	R	R	R	<b>←</b> G —	<b>←</b> Ğ	G	R	R	R	R	R	R	<b>↓</b> ✓	Т
PHASE 2 + 6	G	G	G	G	G	G	R	R	R	R	R	R	<b>◄</b>	
2 + 6 CHANGE	Y	Y	Y	Y	Y	Υ	R	R	R	R	R	R	<u> </u>	- ▶
PHASE 3 + 7	R	R	R	R	R	R		R <b>←</b> G—	R	R <b>←</b> G—	R <b>←</b> G—	R		<u>⊢</u>
3 + 7 CHANGE	PHASE	3 +	7 MAY	CHANC	SE TO	PHASE	3 + 8	3, PHAS	SE 4 +	7 OR	PHASE	= 4 + 8	<b>-</b>	) <sub>T</sub>
PHASE 3 + 8	R	R	R	R	R	R	R	R	R	<b>G</b> <b>G</b> —	<b>G</b> G —	G	<b>1 4</b>	<b>-</b>
3 + 8 CHANGE	R	R	R	R	R	R	R	R	R	<b>←</b> <sup>G</sup> –	<b>←</b> <sup>G</sup> —	G	]- ` )	
PHASE 4 + 7	R	R	R	R	R	R	<b>G</b> —G—	<b>←</b> G—	G	R	R	R		F
4 + 7 CHANGE	R	R	R	R	R	R	<b>←</b> Ğ —	<b>←</b> G —	G	R	R	R	<b>-</b> -  <b>-</b> -  <b>-</b> -	<b>▶</b>
PHASE 4 + 8	R	R	R	R	R	R	G	G	G	G	G	G		
4 + 8 CHANGE	R	R	R	R	R	R	Υ	Y	Υ	Υ	Υ	Y	]-  ↓	
FLASHING OPERATION	FL/Y	FL/Y	FL/Y	FL/Y	FL/Y	FL/Y	FL/R	<b>←</b> FL/R−	<b>←</b> FL/R−	FL/R	FL/R	<b>←</b> FL/R−	<b>4</b>	<b>\</b>

# EQUIPMENT LIST "B"

B. EQUIPMENT TO BE FURNISHED AND/OR INSTALLED BY THE CONTRACTOR

CATEGORY CODE NO.	QUANTITY	DESCRIPTION
203030	2 CY	TEST PIT EXCAVATION
585624	125 LF	24 INCH WHITE HEAT APPLIED PERMANENT PREFORMED THERMOPLASTIC PAVEMENT MARKING
801004	5 CY	FURNISH AND INSTALL CONCRETE FOR SIGNAL FOUNDATION
802501	250 LF	FURNISH AND INSTALL NO. 6 A.W.G. STRANDED BARE COPPER GROUND WIRE
805011	40 LF	FURNISH AND INSTALL 1 INCH GALVANIZED CONDUIT FOR DETECTOR WIRE SLEEVE
80'5118	200 LF	FURNISH AND INSTALL 4 IN. SCHEDULE 80 RIGID PVC CONDUIT - BORED
80/5135	10 LF	FURNISH AND INSTALL 3 IN. SCHEDULE 80 RIGID PVC CONDUIT - TRENCHED
80'5140	40 LF	FURNISH AND INSTALL 4 IN. SCHEDULE 80 RIGID PVC CONDUIT - TRENCHED
81/0550	1 EA	FURNISH AND INSTALL MICROLOOP PROBE SET WITH 500 FOOLLEAD-IN CABLE
810555	1 EA	FURNISH AND INSTALL MICROLOOP PROBE SET WITH 1000 FOLLEAD-IN CABLE
811001	2 EA	FURNISH AND INSTALL ELECTRICAL HANDHOLE
813015	176 SF	INSTALL OVERHEAD SIGN
816001	4 EA	FURNISH AND INSTALL VIDEO DETECTION CAMERA
816005	2 EA	FURNISH AND INSTALL 250 FT. VIDEO DETECTION CABLE
816010	2 EA	FURNISH AND INSTALL 500 FT, VIDEO DETECTION CABLE
837001	1 EA	FURNISH AND INSTALL GROUND ROD - 3/4 INCH DIAMETER x 10 FOOT LENGTH
860270	12 EA	FURNISH AND INSTALL 8 IN. VEHICULAR TRAFFIC SIGNAL HEAD SECTION
860272	42 EA	FURNISH AND INSTALL 12 IN. VEHICULAR TRAFFIC SIGNAL HEAD SECTION
861107	70 LF	FURNISH AND INSTALL ELECTRICAL CABLE - 5 CONDUCTOR (NO. 14 A.W.G)
861108	2000 LF	FURNISH AND INSTALL ELECTRICAL CABLE - 7 CONDUCTOR (NO. 14 A.W.G)
862102	40 LF	FURNISH AND INSTALL SAW CUT FOR SIGNAL (LOOP DETECTO
866205	1 EA	INSTALL STEEL POLE AND TWIN MAST ARM, ANY SIZE
871202	1 EA	INSTALL CONTROLLER AND CABINET - BASE MOUNT
000000	1 LS	REMOVE AND DISPOSE OF EXISTING MATERIAL AND EQUIPMENT
000008	2 EA	INSTALL CONDUIT (UP TO 4 INCHES) BEND IN EXISTING FOUNDATION
DOOD)	LS	Pullback and resource extrem interconnect or

TARSA Whitman, Requardt and Associates, LLP

801 South Caroline Street Baltimore, Maryland 21231 (410) 235-3450 MARYLAND DOT - STATE HIGHWAY ADMINISTRATION
Office of Traffic & Cafet TRAFFIC ENGINEERING DESIGN DIVISION

GENERAL INFORMATION SHEET

INTERSECTION RECONSTRUCTION - MARYLAND ROUTE 589 AT CATHELL ROAD

RAWN BY: <u>B.M.</u> HECKED BY: <u>B.M.</u> Cale: <b>Non</b> e	ARTINE S.	.H.A. NO	WO5035I30 WORCESTER	TS NO.  TS-2290B  T.I.M.S. NO.	SHE	ET NO.
ATE: \$DA	1 0	OG MILE:		F223	15	OF <u>15</u>